

ETAP® FLUTE

Technical Data Sheet

HP FLUTE 1 (Guaranteed Values)

	Basis Weight [g/m ²]	CMT 30,MD [N]	SCT, CD [kN/m]	Moisture %
Standard	T-410	T-809	T-826	T-412
Tolerance	± 3 %	± 5 %	± 5 %	± 1.50 %
	125	260	2.50	7
	135	270	2.70	7
	140	280	2.80	7
	150	300	3.00	7
	175	350	3.50	7
	200	390	4.00	7

HP FLUTE 2 (Guaranteed Values)

	Basis Weight [g/m ²]	CMT 30,MD [N]	SCT, CD [kN/m]	Moisture %
Standard	T-410	T-809	T-826	T-412
Tolerance	± 3 %	± 5 %	± 5 %	± 1.50 %
	125	215	2.30	7
	130	225	2.40	7
	135	235	2.45	7
	140	240	2.55	7
	150	260	2.75	7
	170	290	3.10	7
	175	300	3.15	7
	200	340	3.20	7

Issue Date Jan 2023

BASIC INFORMATION

FSC® certified.

Made from 100% recycled fibers.

Excellent runnability and properties.

Reel diameters: 125 up to 140 cm

Standard Reel core size: 10 cm