

## ETAP® Brown Liner Technical Data Sheet

### LINER 1 (Guaranteed Values)

|           | Basis Weight        | Bursting Strength | SCT, CD | Moisture | Cobb60              |
|-----------|---------------------|-------------------|---------|----------|---------------------|
|           | [g/m <sup>2</sup> ] | [kPa]             | [kN/m]  | %        | [g/m <sup>2</sup> ] |
| Standard  | T-410               | T-807             | T-826   | T-412    | T-441               |
| Tolerance | ± 3 %               | ± 5 %             | ± 5 %   | ± 1.5 %  | Average             |
|           | 125                 | 330               | 2.40    | 7        | 29/35               |
|           | 130                 | 350               | 2.45    | 7        | 29/35               |
|           | 135                 | 360               | 2.50    | 7        | 29/35               |
|           | 140                 | 380               | 2.60    | 7        | 29/35               |
|           | 150                 | 400               | 2.80    | 7        | 29/35               |
|           | 175                 | 440               | 3.10    | 7        | 29/35               |
|           | 200                 | 500               | 3.40    | 7        | 29/35               |

### LINER 2 (Guaranteed Values)

|           | Basis Weight        | Bursting Strength | SCT, CD | Moisture | Cobb60              |
|-----------|---------------------|-------------------|---------|----------|---------------------|
|           | [g/m <sup>2</sup> ] | [kPa]             | [kN/m]  | %        | [g/m <sup>2</sup> ] |
| Standard  | T-410               | T-807             | T-826   | T-412    | T-441               |
| Tolerance | ± 3 %               | ± 5 %             | ± 5 %   | ± 1.5 %  | Average             |
|           | 125                 | 290               | 2.20    | 7        | 29/35               |
|           | 130                 | 310               | 2.30    | 7        | 29/35               |
|           | 135                 | 315               | 2.32    | 7        | 29/35               |
|           | 140                 | 320               | 2.35    | 7        | 29/35               |
|           | 150                 | 350               | 2.40    | 7        | 29/35               |
|           | 175                 | 410               | 2.80    | 7        | 29/35               |
|           | 200                 | 460               | 3.20    | 7        | 29/35               |

Issue Date Jan 2023

#### BASIC INFORMATION

FSC® certified.

Made from 100% recycled fibers.

Excellent runnability and properties.

Reel diameters: 125 up to 140 cm

Standard Reel core size: 10 cm