

## ETAP® White Liner Technical Data Sheet

### White Liner 1 (Guaranteed Values)

Property	Basis Weight	Brightness	Burst	SCT, CD	Moisture	COBB60
	[g/m <sup>2</sup> ]	[%]	[Kpa]	[kN/m]	%	[g/m <sup>2</sup> ]
Standard	T-410	ISO 2470	T-807	T-826	T-412	T-441
Tolerance	± 3 %	± 2 %	± 5 %	± 5 %	± 1 %	Average
	125	82	295	2.10	7	30-35
	140	85	350	2.50	7	30-35

### White Liner 2 (Guaranteed Values)

Property	Basis Weight	Brightness	Burst	SCT, CD	Moisture	COBB60
	[g/m <sup>2</sup> ]	[%]	[Kpa]	[kN/m]	%	[g/m <sup>2</sup> ]
Standard	T-410	ISO 2470	T-807	T-826	T-412	T-441
Tolerance	± 3 %	± 2 %	± 5 %	± 5 %	± 1 %	Average
	125	75	290	2.00	7	30-35
	140	75	330	2.30	7	30-35

Issue Date Dec 2022

#### BASIC INFORMATION

FSC® certified.

Made from 100% recycled fibers.

Excellent runnability , properties and Printability .

Reel diameters: 125 up to 140 cm

Standard Reel core size: 10 cm or 7 cm